

Tabelle contropressioni

Valori misurati all'interno di una condotta in metallo asciutta

Palloni otturatori mini

Diametro mm	RDK 2,5/4 1440000101	RDK 4/7 1440000201	RDK 7/10 1440025900	RDK 8/15 1440018800	RDK 10/15 1440010500	RDK 12,5/20 1440010700	RDK 15/20 1440018900	RDK 15/30 1440010600
2,5 bar								
25	1,6							
40	1,4							
50		1,65						
70		1,25						
80			1,3	1,35				
90			1,3	1,25				
100			1,3	1,25	1,4			
125				1,25	1,35		1,4	
150				1,05	1,3	1,15	1,3	1,35
200						1,1	1,25	1,3
250								1,25
300								1,25

Palloni otturatori

Diametro mm	RDK 7/15 1440000301 1440008100 (CR)	RDK 10/20 1440011700	RDK 15/30 1440000601 1440008000 (CR)	RDK 20/40 1440020100	RDK 20/50 1440016700	RDK 30/60 1440000801 1440007900 (CR)	RDK 50/100 1440028200
2,5 bar							
70	2,1						
80	2						
90	1,8						
100	1,7	2,4					
125	1,6	2,0					
150	1,1	1,85	2,4				
200		1,3	2,1	2,3	2,2		
250			1,5	2,3	2		
300			1,0	2,1	2	2,3	
400				1,9	1,9	2	
500					1,7	1,9	2,05
600						1,6	1,95
800							1,60
1.000							1,2

Diametro mm	RDK 60/120 1480001901 1480004800 (CR)	RDK 80/140 1480006000
1,5 bar		
600	1,1	
800	0,95	0,5
1.000	0,85	0,5
1.200	0,75	0,5
1.400		0,5

Diametro mm	RDK 140/170 1400000300	RDK 170/200 1400000100
0,5 bar		
500		
600		
800		
1.000		
1.200		
1.400	0,2	
1.700	0,2	0,2
2.000	0,2	0,2

Palloni otturatori mini con by-pass

Diametro mm	PDK 4/7 1441000701	PDK 7/10 1441043900	PDK 10/15 1441035400	PDK 15/20 1441035200	PDK 20/30 1441035300
2,5 bar					
25					
40	1,8				
50	1,6				
70	1,3	1,3			
80		1,3			
90		1,3			
100		1,3	1,5		
125			1,25		
150			1,2	1,3	
200				1,2	1,25
250					1,25
300					1,25

Tutte le contropressioni sono indicate in bar.

Palloni otturatori con by-pass

Diametro mm	PDK 4/7 FLEX 1441000701	PDK 7/15 FLEX 1441001201	PDK 10/20 FLEX 1441018501	PDK 15/30 FLEX 1441022701 1441022800	PDK 20/40 FLEX 1441040300 1441018600	PDK 20/50 FLEX 1441031100 1441031200	PDK 30/60 FLEX 1441023100 1441018701
----------------	----------------------------	-----------------------------	------------------------------	--	--	--	--

2,5 bar

40	1,3						
70	1,3	1,55					
80		1,75					
90		1,7					
100		1,65	1,6				
125		1,5	1,5				
150		1,4	1,4	1,65			
200			1,45	1,6	1,45	2	
250				1,5	1,3	1,7	
300				1,3	1,35	1,65	1,6
400					1,3	1,5	1,65
500						1,35	1,4
600							1,3
800							
1.000							
1.200							
1.400							
1.700							
2.000							

Diametro mm	PDK 50/100 FLEX 1481003501 1481023800	PDK 60/120 FLEX 1481009501 1481009301	PDK 80/140 FLEX 1481024000 1481023900
----------------	---	---	---

1,5 bar

500	1,2		
600	1,2	1,05	
800	1	0,9	0,5
1.000	0,55	0,8	0,5
1.200		0,75	0,5
1.400			0,5
1.700			
2.000			

Diametro mm	PDK 140/170 FLEX 1401000400 1401000300	PDK 170/200 FLEX 1401000700 1401000600
----------------	--	--

0,5 bar

500		
600		
800		
1.000		
1.200		
1.400	0,2	
1.700	0,2	0,2
2.000	0,2	0,2

Distribuito da

HANS BRAND

info@hansbrand.it
www.hansbrand.it

Tutte le contropressioni sono indicate in bar.